

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 May 2003 (15.05.2003)

PCT

(10) International Publication Number
WO 03/040273 A2

(51) International Patent Classification⁷: **C10M 163/00** //
(C10M 163/00, 159:24, 159:22, 129:10, 129:76, 133:12,
135:04, 135:06, 137:10), C10N 10/04, 40/25

(US). **KELLEY, Jack, C.** [US/US]; 8860 Peppermill Run,
Chagrin Falls, OH 44023 (US).

(21) International Application Number: PCT/US02/33117

(74) Agents: **SHOLD, David, M.** et al.; The Lubrizol Corpo-
ration, 29400 Lakeland Boulevard, Wickliffe, OH 44092-
2298 (US).

(22) International Filing Date: 15 October 2002 (15.10.2002)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/337,720 5 November 2001 (05.11.2001) US

(71) Applicant (*for all designated States except US*): **THE LU-
BRIZOL CORPORATION** [US/US]; 29400 Lakeland
Boulevard, Wickliffe, OH 44092-2298 (US).

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE, SK, TR).

Published:

— *without international search report and to be republished
upon receipt of that report*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WILK, Melody, A.**
[US/US]; 90 East Shore Boulevard, Timberlake, OH 44095
(US). **DOHNER, Brent, R.** [US/US]; 10320 Springbrook
Court, Concord, OH 44077 (US). **ZALAR, Frank, V.**
[US/US]; 13619 Fox Hills Drive, Novelty, OH 44072

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: SULFONATE DETERGENT SYSTEM FOR IMPROVED FUEL ECONOMY

(57) Abstract: A composition for lubricating an internal combustion engine includes an oil of lubricating viscosity; a predominantly linear alkylbenzenesulfonate detergent having a metal ratio of at least 8; and a combination of hindered phenolic ester antioxidant and aromatic amine antioxidant. The amount of any phenate detergent is less than 15% by weight of the total amount of detergents.

WO 03/040273 A2

TITLE

Sulfonate Detergent System for Improved Fuel Economy

BACKGROUND OF THE INVENTION

5 [0001] The present invention relates to a composition and method for lubricating an internal combustion engine, providing improved fuel economy and retention of fuel economy.

[0002] Fuel economy is of great importance, and lubricants which can foster improved fuel economy, by, for instance, leading to reduced friction within an engine, are of significant value. The present invention provides a lubricant
10 composition, including an additive package, which leads to improved fuel economy in an internal combustion engine. This improvement is effected by providing an additive package in which the detergent component is exclusively or predominantly an alkylsulfonate.

15 [0003] U.S. Patent 4,952,328, Davis et al., August 28, 1990, discloses lubricating oil compositions for internal combustion engines, comprising (A) oil of lubricating viscosity, (B) a carboxylic derivative produced by reacting a succinic acylating agent with certain amines, and (C) a basic alkali metal salt of sulfonic or carboxylic acid. An illustrative lubricant composition (Lubricant III) includes
20 base oil including viscosity index modifier; a basic magnesium alkylated benzene sulfonate; an overbased sodium alkylbenzene sulfonate; a basic calcium alkylated benzene sulfonate; succinimide dispersant; and zinc salts of a phosphorodithioic acids.

[0004] U.S. Patent 4,326,972, Chamberlin, April 27, 1982, discloses lubricant
25 compositions for improving fuel economy of internal combustion engines. The composition includes a specific sulfurized composition (based on an ester of a carboxylic acid) and a basic alkali metal sulfonate. Additional ingredients may include at least one oil-dispersible detergent or dispersant, a viscosity improving agent, and a specific salt of a phosphorus acid.

30 [0005] US. Patent 3,994,815, Coleman, November 30, 1976, discloses lubricating compositions. Disclosed in an example is an additive concentrate prepared using a polyisobutylene synthetic lubricating oil containing a hydrogenated butadiene-styrene copolymer; a dispersant; a zinc isobutylamyl phosphorodithioate, an overbased calcium sulfonate detergent, and an anti-foaming agent.

SUMMARY OF THE INVENTION

35 [0006] The present invention provides a composition suitable for lubricating an internal combustion engine, comprising the following components:

- (a) an oil of lubricating viscosity;
- (b) an overbased detergent, wherein the detergent is exclusively or predominantly a linear alkylbenzenesulfonate detergent having a metal ratio of at least 8, wherein in said composition the amount of phenate detergent is less than 15% by weight of the total amount of detergents
- (c) a combination of antioxidants comprising
- (i) 0.1 to 2 weight percent hindered phenolic ester antioxidant and
- (ii) 0.2 to 2 weight percent aromatic amine antioxidant; and
- (d) at least one further component selected from the group consisting of dispersants, zinc dialkyldithiophosphates, and friction modifiers.
- [0007] The invention also provides a method for lubricating an internal combustion engine, comprising supplying to such engine the lubricant described above.
- [0008] The invention also provides a concentrate comprising a concentrate-forming amount of an oil of lubricating viscosity and corresponding amounts of components (b), (c), and (d).

DETAILED DESCRIPTION OF THE INVENTION

- [0009] Various preferred features and embodiments will be described below by way of non-limiting illustration.
- [0010] Component (a) is an oil of lubricating viscosity, which term includes natural or synthetic lubricating oils and mixtures thereof. Natural oils include animal oils, vegetable oils, mineral lubricating oils, solvent or acid treated mineral oils, and oils derived from coal or shale. Synthetic lubricating oils include hydrocarbon oils, halo-substituted hydrocarbon oils, alkylene oxide polymers, esters of dicarboxylic acids and polyols, esters of phosphorus-containing acids, polymeric tetrahydrofurans and silicon-based oils.
- [0011] Specific examples of the oils of lubricating viscosity are described in U.S. Patent 4,326,972 and European Patent Publication 107,282. A basic, brief description of lubricant base oils appears in an article by D. V. Brock, "Lubricant Base Oils", Lubrication Engineering, Volume 43, pages 184-185, March, 1987. A description of oils of lubricating viscosity occurs in U.S. Patent 4,582,618 (column 2, line 37 through column 3, line 63, inclusive).
- [0012] The oils used in the present invention can preferably be API Group II or Group III oils. These are generally mineral oil based oils which are relatively low in sulfur content and high in saturate content. Group II oils contain ≤ 0.03 % sulfur and ≥ 90 % saturates and a viscosity index of 80 to 120. Group III oils

are similar but have a viscosity index of ≥ 120 . Excluded from these categories are polyalphaolefins, which are separately categorized as Group IV.

5 [0013] The lubricating oil in the invention will normally comprise the major amount of the composition. Thus it will normally be at least 50% by weight of the composition, preferably about 83 to about 98%, and most preferably about 88 to about 90%. As an alternative embodiment, however, the present invention can provide an additive concentrate in which the oil can be 0 to about 20% by weight, preferably about 1 to about 10%, and the other components, described in greater detail below, are proportionately increased.

10 [0014] Component (b) is a detergent which is predominantly or exclusively a sulfonate detergent. These are specifically overbased materials, and specifically overbased alkylbenzenesulfonate detergents, more particularly linear alkylbenzenesulfonate detergents.

15 [0015] Overbased materials are single phase, homogeneous Newtonian systems characterized by a metal content in excess of that which would be present according to the stoichiometry of the metal and the particular acidic organic compound reacted with the metal.

20 [0016] The amount of excess metal is commonly expressed in terms of metal ratio. The term "metal ratio" is the ratio of the total equivalents of the metal to the equivalents of the acidic organic compound. A neutral metal salt has a metal ratio of one. A salt having 4.5 times as much metal as present in a normal salt will have metal excess of 3.5 equivalents, or a ratio of 4.5. The metal ratio for a sulfonate detergent is calculated based on the ratio of metal to the sulfonate functionality, ignoring the presence of any other incidental acidic groups that may be present in the detergent molecule. The metal ratio of the sulfonate detergents used in the present invention will typically be at least 8, for example, 8 to 35, preferably 10 to 30 or 15 to 25, or, in one instance, about 20.

25 [0017] The basicity of the overbased materials of the present invention generally is expressed in terms of a total base number. A total base number is the amount of acid (perchloric or hydrochloric) needed to neutralize all of the overbased material's basicity. The amount of acid is expressed as potassium hydroxide equivalents (mg KOH per gram of sample). The overbased materials generally have a total base number up to 600, preferably 500, more preferably 400. In a preferred embodiment, the TBN of the sulfonate is 300 to 500, preferably about 400.

35 [0018] The overbased materials are prepared by reacting an acidic material (typically an inorganic acid or lower carboxylic acid, preferably carbon dioxide)

with a mixture comprising an acidic organic compound, a reaction medium comprising at least one inert, organic solvent (such as mineral oil, naphtha, toluene, or xylene) for said acidic organic material, a stoichiometric excess of a metal base, and a promoter.

5 [0019] The acidic organic compounds useful in making the overbased compositions generally can include carboxylic acids, sulfonic acids, phosphorus-containing acids, phenols or mixtures of two or more thereof. For purposes of the present invention, the acidic organic compounds are sulfonic acids.

[0020] The sulfonic acids useful in making the overbased salts of the invention
10 include the sulfonic and thiosulfonic acids. Generally they are salts of sulfonic acids. The sulfonic acids include the mono- or polynuclear aromatic or cycloaliphatic compounds. The oil-soluble sulfonates can be represented for the most part by one of the following formulae: $R_2-T-(SO_3^-)_a$ and $R_3-(SO_3^-)_b$, wherein T is a cyclic nucleus such as, for example, benzene, naphthalene, anthracene, diphenylene oxide, diphenylene sulfide, or petroleum naphthenes; R_2 is an aliphatic group such as alkyl, alkenyl, alkoxy, or alkoxyalkyl; $(R_2)+T$ contains a total of at least 15 carbon atoms; and R_3 is an aliphatic hydrocarbyl group containing at least 15 carbon atoms. Examples of R_3 are alkyl, alkenyl, alkoxyalkyl, and carboalkoxyalkyl. Specific examples of R_3 are groups derived from petrolatum, saturated and unsaturated paraffin wax, and the above-described polyalkenes. The groups T, R_2 , and R_3 in the above formulas can also contain other inorganic or organic substituents in addition to those enumerated above such as, for example, hydroxy, mercapto, halogen, nitro, amino, nitroso, sulfide, disulfide, etc. In the above formulas, a and b are at least 1. In one embodiment, the sulfonic acids have
20 a substituent (R_2 or R_3) which is derived from one of the above-described polyalkenes.

[0021] Illustrative examples of these sulfonic acids include monoeicosanyl-substituted naphthalene sulfonic acids, dodecylbenzene sulfonic acids, didodecylbenzene sulfonic acids, dinonylbenzene sulfonic acids, dilauryl beta-naphthalene sulfonic acids, the sulfonic acid derived by the treatment of polybutene having a number average molecular weight (\overline{M}_n) in the range of 500 to 5000, preferably 800 to 2000, more preferably about 1500, with chlorosulfonic acid, nitronaphthalene sulfonic acid, paraffin wax sulfonic acid, cetyl-cyclopentane sulfonic acid, lauryl-cyclohexane sulfonic acids, polyethylenyl-substituted sulfonic acids derived from polyethylene ($\overline{M}_n = 300-1000$, preferably 750). Normally the aliphatic groups will be alkyl and/or alkenyl groups such that the total number of aliphatic carbons is at least 8, preferably at least 12 up to
35

400 carbon atoms, preferably up to 250. In a preferred embodiment, the substituent will be an alkyl group having an appropriate length such that the molecular weight of the alkylbenzene group is 320 to 700 or, more narrowly 380 to 420.

5 [0022] Another group of sulfonic acids are mono-, di-, and tri-alkylated benzene and naphthalene (including hydrogenated forms thereof) sulfonic acids. Illustrative of synthetically produced alkylated benzene and naphthalene sulfonic acids are those containing alkyl substituents having 8 to 30 carbon atoms, preferably 12 to 30 carbon atoms, and advantageously about 24 carbon atoms. Such
10 acids include di-isododecyl-benzenesulfonic acid, polybutenyl-substituted benzenesulfonic acid, polypropylenyl-substituted benzenesulfonic acids derived from polypropene having an $\overline{M}_n=300-1000$, preferably 500-700, cetylchlorobenzene sulfonic acid, di-cetylnaphthalene sulfonic acid, di-lauryldiphenylether sulfonic acid, diisononylbenzene sulfonic acid, di-isooctadecylbenzene sulfonic
15 acid, or stearyl naphthalene sulfonic acid.

[0023] Specific examples of oil-soluble sulfonic acids are mahogany sulfonic acids; bright stock sulfonic acids; sulfonic acids derived from lubricating oil fractions having a Saybolt viscosity from 100 seconds at 38°C (100°F) to 200 seconds at 99°C (210°F); petrolatum sulfonic acids; mono- and poly-wax-substituted
20 sulfonic and polysulfonic acids of, e.g., benzene, naphthalene, phenol, diphenyl ether, or naphthalene disulfide; other substituted sulfonic acids such as alkyl benzene sulfonic acids (where the alkyl group has at least 8 carbons), cetylphenol mono-sulfide sulfonic acids, dilauryl beta naphthyl sulfonic acids, and alkaryl sulfonic acids such as dodecyl benzene bottoms sulfonic acids.

25 [0024] Sulfonate detergents can also be characterized generally as based on either natural sulfonates or on synthetic sulfonates. In both instances, alkylaromatic sulfonates typically predominate. Natural sulfonates tend to contain at least a minimal amount of polycyclic species. Natural sulfonic acids are typically prepared by sulfonation of suitable petroleum fractions. Synthetic sulfonates, on the other hand, tend to be monocyclic species, mono or di-alkylated.
30 Synthetic alkaryl sulfonic acids are typically prepared from alkylated benzenes such as the Friedel-Crafts reaction products of benzene and alkyl-group providing agents such as tetrapropylene.

[0025] The production of sulfonates from detergent manufactured
35 by-products by reaction with, e.g., SO_3 , is well known to those skilled in the art. See, for example, the article "Sulfonates" in Kirk-Othmer "Encyclopedia of

Chemical Technology", Second Edition, Vol. 19, pp. 291 et seq. published by John Wiley & Sons, N.Y. (1969).

[0026] The metal compounds useful in making the basic metal salts are generally any Group 1 or Group 2 metal compounds (CAS version of the Periodic Table of the Elements). The Group 1 metals of the metal compound include Group 1a alkali metals (such as sodium, potassium, lithium) as well as Group 1b metals such as copper. The Group 1 metals are preferably sodium, potassium, lithium and copper, more preferably sodium or potassium, and more preferably sodium. The Group 2 metals of the metal base include the Group 2a alkaline earth metals (such as magnesium, calcium, barium) as well as the Group 2b metals such as zinc or cadmium. Preferably the Group 2 metals are magnesium, calcium, barium, or zinc, preferably magnesium or calcium, more preferably calcium. A preferred metal is calcium, and the metal can be solely calcium. In a preferred embodiment the composition will contain less than 500, or less than 400, or less than 300 parts per million by weight of metals other than calcium or zinc (the zinc normally being derived from the zinc dialkyldithiophosphate which may be present.) Generally the metal compounds are delivered as metal salts. The anionic portion of the salt can be, e.g., hydroxide, oxide, carbonate, borate, or nitrate.

[0027] An acidic gas is employed to accomplish the formation of the basic metal salt (A). The acidic gas is preferably carbon dioxide, or sulfur dioxide, and is most preferably carbon dioxide.

[0028] Patents specifically describing techniques for making basic salts of the above-described sulfonic acids, as well as carboxylic acids, and mixtures of any two or more of these include U.S. Patents 2,501,731; 2,616,905; 2,616,911; 2,616,925; 2,777,874; 3,256,186; 3,384,585; 3,365,396; 3,320,162; 3,318,809; 3,488,284; and 3,629,109.


[0029] The overbased salt may also be a borated complex. Borated complexes of this type can be prepared by heating the basic metal salt with boric acid at about 50 – 100°C, the number of equivalents of boric acid being roughly equal to the number of equivalents of metal in the salt. U.S. Patent No. 3,929,650 discloses borated complexes and their preparation

[0030] The amount of component (b) in the compositions of the present invention is generally greater than 0.28 percent by weight (on an oil-free basis), preferably at least 0.3, 0.35, or 0.4 percent. The upper amount of this component is not particularly critical, although amounts greater than 1% or 2% in the final lubricating composition

are not believed to provide much additional advantage in many circumstances. Of course, these amounts will be correspondingly increased in a concentrate.

[0031] In addition to the sulfonate detergent, relatively small amounts of one or more additional detergents can be present. While the presence of phenate detergent as such is not particularly favored, such other detergents as salicylate detergents, saligenin detergents, or salixarate detergents can be, but need not be, present. Salicylate detergents are typically overbased metal salts of alkyl-substituted salicylic acid. These materials are commercially available, for instance, from Shell Oil Company under the tradenames Sap 007 or AC-60. Calcium and magnesium overbased salicylate detergents are known


[0032] Saligenin detergents are typically overbased metal salts of saligenin derivatives, that is, salts of the condensation product of a hydrocarbyl-substituted phenol with an aldehyde such as formaldehyde. They may be represented by the general structure




wherein X comprises $-\text{CHO}$ or $-\text{CH}_2\text{OH}$, Y comprises $-\text{CH}_2-$ or $-\text{CH}_2\text{OCH}_2-$, and wherein such $-\text{CHO}$ groups comprise at least 10 mole percent of the X and Y groups; M is a mono- or di- valent metal ion such as sodium, calcium, or magnesium. Each n is independently 0 or 1. R^1 is a hydrocarbyl group containing 1 to 60 carbon atoms, m is 0 to 10, and when $m > 0$, one of the X groups can be H; each p is independently 0, 1, 2 or 3, preferably 1; and that the total number of carbon atoms in all R^1 groups is at least 7.

[0033] Saligenin detergents and their method of preparation, including their structure, preferred metal ions, extent of neutralization, and preferred amounts and ratios of formaldehyde-derived groups ($-\text{CH}_2\text{OCH}_2-$, $-\text{CH}_2-$, $-\text{CHO}$, and $-\text{CH}_2\text{OH}$) are described in greater detail in U.S. Patent No. 6,310,009.

[0034] Salixarate detergents are typically the overbased metal salts (typical metals, as described above, such as sodium, calcium, magnesium) of compounds comprising at least one unit of formula (I) or formula (II):




(I)




(II)

each end of the compound having a terminal group of formula (III) or (IV):



(III)



(IV)

5

10

15

such groups being linked by divalent bridging groups A, which may be the same or different for each linkage. In formulas (I)-(IV) R³ is hydrogen or a hydrocarbyl group; R² is hydroxyl or a hydrocarbyl group, and j is 0, 1, or 2; R⁶ is hydrogen, a hydrocarbyl group, or a hetero-substituted hydrocarbyl group; either R⁴ is hydroxyl and R⁵ and R⁷ are independently either hydrogen, a hydrocarbyl group, or hetero-substituted hydrocarbyl group, or else R⁵ and R⁷ are both hydroxyl and R⁴ is hydrogen, a hydrocarbyl group, or a hetero-substituted hydrocarbyl group. Preferably at least one of R⁴, R⁵, R⁶ and R⁷ is hydrocarbyl containing at least 8 carbon atoms. The molecules on average contain at least one of unit (I) or (III) and at least one of unit (II) or (IV) and the ratio of the total number of units (I)

and (III) to the total number of units of (II) and (IV) in the composition is about 0.1:1 to about 2:1.


[0035] The divalent bridging group "A," which may be the same or different in each occurrence, includes $-\text{CH}_2-$ and $-\text{CH}_2\text{OCH}_2-$, either of which may be derived from formaldehyde or a formaldehyde equivalent.

[0036] Salixarate derivatives and methods of their preparation are described in greater detail in U.S. patent number 6,200,936 and PCT Publication WO 01/56968. The salixarate derivatives may have a predominantly linear, rather than macrocyclic, structure, although both structures are envisioned.

[0037] The amount of detergents based on other acidic materials, such as carboxylates, phenates, salicylates, saligenins, or salixarates, should be less than 30% of the total amount of detergent component, or alternatively of the sulfonate detergent, and preferably less than 20%, 15%, 10%, 5%, or 1%. In particular, the amount of any phenate detergents should be less than 15% of the detergents or, alternatively of the sulfonate detergent.

[0038] Other additives are preferably included within the lubricating composition. Among these are dispersants, metal salts of phosphorus acids, antioxidants, and friction modifiers such as glycerol monooleate.

[0039] Dispersants are well known in the field of lubricants and include primarily what are sometimes referred to as ashless-type dispersants and polymeric dispersants. Ashless type dispersants are so-called because they themselves do not contain ash-forming metals. However, it is known that when mixed with metal-containing components, they may associate with the metals and are no longer technically "ashless." However, they are still to be understood to be "ashless type dispersants" and may be referred to as such. They are characterized by a polar group attached to a relatively high molecular weight hydrocarbon chain. Typical ashless dispersants include N-substituted long chain alkenyl succinimides, having a variety of chemical structures including typically




where each R^1 is independently an alkyl group, frequently a polyisobutyl group with a molecular weight of 500-5000, and R^2 are alkenyl groups, commonly ethylenyl (C_2H_4) groups. Such molecules are commonly derived from reaction of an alkenyl acylating agent with a polyamine, and a wide variety of linkages

between the two moieties is possible beside the simple imide structure shown above, including a variety of amides and quaternary ammonium salts. Succinimide dispersants are more fully described in U.S. Patents 4,234,435 and 3,172,892, with particular reference to the teaching relating to number of succinic groups per chain and molecular weight limitations of the former patent. In particular, certain desirable dispersants will be based on an acylating agent having substituent groups derived from a polyalkene (such as polyisobutene) characterized by a \overline{M}_n value of 1300 or 1500 to 5000 and a $\overline{M}_w/\overline{M}_n$ value of 1.5 or 1.8 to 4, e.g., 2.0 to 3.4 or 2.5 to 3.2. Such acylating agents will be characterized by the presence within their structure of an average of at least 1.3 (e.g., 1.5 to 2.5) succinic groups for each equivalent weight of substituent groups. The number of equivalent weight of substituent groups is deemed to be the number corresponding to the quotient obtained by dividing the \overline{M}_n value of the polyalkene from which the substituent is derived into the total weight of the substituent groups present in the substituted succinic acylating agent. Thus, if a substituted succinic acylating agent is characterized by a total weight of substituent group of 40,000 and the \overline{M}_n value for the polyalkene from which the substituent groups are derived is 2000, then that total succinic acylating agent is characterized by at total of 20 (40,000/2000 = 20) equivalent weights of substituent groups. Therefore, that particular succinic acylating agent would also be characterized by the presence within its structure of at least 26 succinic groups.

[0040] Another class of dispersant is high molecular weight esters. These materials are similar to the above-described succinimides except that they may be seen as having been prepared by reaction of a hydrocarbyl acylating agent and a polyhydric aliphatic alcohol such as glycerol, pentaerythritol, or sorbitol. Such materials are described in more detail in U.S. Patent 3,381,022.

[0041] Another class of dispersant is Mannich bases. These are materials which are formed by the condensation of a higher molecular weight, alkyl substituted phenol, an alkylene polyamine, and an aldehyde such as formaldehyde. Such materials may have the general structure



(including a variety of isomers and the like) and are described in more detail in U.S. Patent 3,634,515.


[0042] Other dispersants include polymeric dispersant additives, which are generally hydrocarbon-based polymers which contain polar functionality to impart dispersancy characteristics to the polymer.

[0043] Dispersants can also be post-treated by reaction with any of a variety of agents. Among these are urea, thiourea, dimercaptotriazoles, carbon disulfide, aldehydes, ketones, carboxylic acids, hydrocarbon-substituted succinic anhydrides, nitriles, epoxides, boron compounds, and phosphorus compounds.


References detailing such treatment are listed in U.S. Patent 4,654,403.

[0044] The amount of the dispersant, if present, is typically 0.5 to 5 percent by weight, preferably 1 to 4 or 2 to 3 percent by weight. Its amount in a concentrate can be correspondingly increased.


[0045] The metal salts of phosphorus acids include metal salts of the formula



wherein R^8 and R^9 are independently hydrocarbyl groups containing 3 to 30 carbon atoms are readily obtainable by the reaction of phosphorus pentasulfide (P_2S_5) and an alcohol or phenol to form an O,O-dihydrocarbyl phosphorodithioic acid corresponding to the formula



[0046] The reaction involves mixing at a temperature of 20°C to 200°C, four moles of an alcohol or a phenol with one mole of phosphorus pentasulfide. Hydrogen sulfide is liberated in this reaction. The acid is then reacted with a basic metal compound to form the salt. The metal M, having a valence n, generally is aluminum, lead, tin, manganese, cobalt, nickel, zinc, or copper, and most preferably zinc. The basic metal compound is thus preferably zinc oxide, and the resulting metal compound is represented by the formula



[0047] The R⁸ and R⁹ groups are independently hydrocarbyl groups that are preferably free from acetylenic and usually also from ethylenic unsaturation. They are typically alkyl, cycloalkyl, aralkyl or alkaryl group and have 3 to 20 carbon atoms, preferably 3 to 16 carbon atoms and most preferably up to 13 carbon atoms, e.g., 3 to 12 carbon atoms. The alcohol which reacts to provide the R⁸ and R⁹ groups can be a mixture of a secondary alcohol and a primary alcohol, for instance, preferably a mixture of isopropanol and 4-methyl-2-pentanol. In a preferred embodiment the alcohol mixture comprises 50% or more secondary alcohols, for instance, 50% or more isopropanol. Among specific mixtures of alcohols are 40:60 and 60:40 molar mixtures of 4-methyl-2-pentanol and isopropanol and similar mixtures of 2-ethylhexanol and isopropanol and of iso-octanol and isopropanol.


[0048] Such materials are often referred to as zinc dialkyldithiophosphates or simply zinc dithiophosphates. They are well known and readily available to those skilled in the art of lubricant formulation.

[0049] The amount of the metal salt of a phosphorus acid in a completely formulated lubricant, if present, can typically be 0.1 to 4 percent by weight, preferably 0.5 to 2 percent by weight, and more preferably 0.75 to 1.25 percent by weight. Its concentration in a concentrate will be correspondingly increased, to, e.g., 5 to 20 weight percent. Alternatively, expressed, the amount of such compound, e.g., a zinc dialkyldithiophosphate, will be an amount to deliver 0.025 to 0.1 weight percent, or 0.35 to 0.8 weight percent, phosphorus to the overall composition.


[0050] In a further embodiment, the lubricating oil composition may contain one or more antioxidants. Antioxidants for use in lubricant compositions are well known and include a variety of chemical types including phenate sulfides, phosphosulfurized terpenes, sulfurized esters, aromatic amines, and hindered phenols.

[0051] Aromatic amine are typically of the formula

13




- wherein R^5 is a phenyl group or a phenyl group substituted by R^7 , and R^6 and R^7 are independently a hydrogen or an alkyl group containing 1 to 24 carbon atoms. Preferably R^5 is a phenyl group substituted by R^7 and R^6 and R^7 are alkyl groups containing from 4 to 20 carbon atoms. In one embodiment the antioxidant can be an alkylated diphenylamine such as nonylated diphenylamine of the formula



- 10 [0052] The amount of the aromatic phenol antioxidant is generally 0.2 to 2 weight percent of the composition, preferably 0.3 to 1.5 weight percent or 0.4 to 1 weight percent.

[0053] Hindered phenol antioxidants are typically alkyl phenols of the formula




15

- wherein R^4 is an alkyl group containing 1 up to 24 carbon atoms and a is an integer of 1 to 5. Preferably R^4 contains 4 to 18 carbon atoms and most preferably from 4 to 12 carbon atoms. R^4 may be either straight chained or branched chained; branched chained is generally preferred. The preferred value for a is an integer of 1 to 4 and most preferred 1 to 3 or, particularly, 2. Preferably the phenol is a


20

butyl substituted phenol containing 2 or 3 t-butyl groups. When a is 2, the t-butyl groups occupy the 2,6-position, that is, the phenol is sterically hindered:


[0054] A particularly preferred antioxidant is a hindered, ester-substituted



5 phenol such as one represented by the formula



and more preferably



10

wherein R^3 is a straight chain or branched chain alkyl group containing 2 to 22 carbon atoms, preferably 2 to 8, 2 to 6, or 4 to 8 carbon atoms and more preferably 4 or 8 carbon atoms. R^3 is desirably a 2-ethylhexyl group or an n-butyl group.

15 [0055] Hindered, ester-substituted phenols can be prepared by heating a 2,6-dialkylphenol with an acrylate ester under base catalysis conditions, such as aqueous KOH.

[0056] The amount of the hindered phenolic ester antioxidant is generally 0.1 to 2 weight percent of the composition, preferably 0.2 to 1.5 weight percent or 20 0.3 to 1 weight percent.

[0057] In one embodiment, the antioxidant component of the composition further comprises a sulfurized olefin antioxidant. Such materials are commer-

cially known and are generally formed by treatment of an olefin or a compound containing olefinic unsaturation with sulfur or a sulfurizing agent. The olefinic compounds which may be sulfurized are diverse in nature. They contain at least one olefinic double bond, that is, a non-aromatic double bond connecting two aliphatic carbon atoms. In its broadest sense, the olefin may be defined by the formula $R^1R^2C=CR^3R^4$, wherein each of R^1 , R^2 , R^3 and R^4 is hydrogen or an organic group, any two of which may also together form a cyclic alkylene or substituted alkylene group; i.e., the olefinic compound may be alicyclic. In another embodiment, one of the R groups can contain an ester function, e.g., the sulfurized olefin can be sulfurized 4-carbobutoxy cyclohexene.

[0058] The olefinic compound is usually one in which each R group which is not hydrogen is independently alkyl, alkenyl or aryl group. Monoolefinic and diolefinic compounds, particularly the former, are preferred, and especially terminal monoolefinic hydrocarbons. Olefinic compounds having about 3 to 30 and especially about 3 to 16 (most often less than 9) carbon atoms are particularly desirable.

[0059] Isobutene, propylene and their dimers, trimers and tetramers, and mixtures thereof can be suitable olefinic compounds. In another embodiment, the sulfurized organic compound can be a sulfurized terpene compound.

[0060] In one embodiment, sulfurized olefins are produced by (1) reacting sulfur monochloride with a stoichiometric excess of a low carbon atom olefin, (2) treating the resulting product with an alkali metal sulfide in the presence of free sulfur in a mole ratio of no less than 2:1 in an alcohol-water solvent, and (3) reacting that product with an inorganic base. This procedure is described in U.S. Patent 3,471,404. The sulfurized olefins also may be prepared by the reaction, under superatmospheric pressure, of olefinic compounds with a mixture of sulfur and hydrogen sulfide in the presence of a catalyst, followed by removal of low boiling materials. This procedure is described in U.S. Patent 4,191,659. The reaction can also be conducted by addition of flowers of sulfur to the olefin at atmospheric pressure, followed by heating. Resulting H_2S can be removed from the mixture by washing with NaOH solution.

[0061] The amount of the sulfurized olefin antioxidant is generally 0.1 to 1 weight percent, preferably 0.2 to 0.8 weight percent. The total amount of the various antioxidants can typically be 0.3 to 5 percent by weight of the composition, commonly 0.4 to 4 percent by weight, or to 2 percent or to 1 percent, and typically 0.5 to 0.7 percent.

[0062] The compositions of the present invention may also include, or exclude, other components which are commonly found in lubricating compositions. For instance, corrosion inhibitors, extreme pressure agents, and anti-wear agents include but are not limited to chlorinated aliphatic hydrocarbons; boron-containing compounds including borate esters; and molybdenum compounds. Viscosity improvers include but are not limited to polyisobutenes, polymethacrylate acid esters, polyacrylate acid esters, diene polymers, polyalkyl styrenes, alkenyl aryl conjugated diene copolymers, polyolefins and multifunctional viscosity improvers, including dispersant viscosity modifiers (which impart both dispersancy and viscosity improvement). Pour point depressants are a particularly useful type of additive, often included in the lubricating oils described herein usually comprising substances such as polymethacrylates, styrene-based polymers, crosslinked alkyl phenols, or alkyl naphthalenes,. See for example, page 8 of "Lubricant Additives" by C. V. Smalheer and R. Kennedy Smith (Lesius-Hiles Company Publishers, Cleveland, Ohio, 1967). Anti-foam agents used to reduce or prevent the formation of stable foam include silicones or organic polymers. Examples of these and additional anti-foam compositions are described in "Foam Control Agents", by Henry T. Kerner (Noyes Data Corporation, 1976), pages 125-162. These and other additives which may be used in combination with the present invention are described in greater detail in U.S. Patent 4,582,618 (column 14, line 52 through column 17, line 16, inclusive)

[0063] The composition described above is prepared by mixing the components. The order or manner of mixing is not considered to be particularly important.

25 EXAMPLES

[0064] The following formulations are prepared in an oil of lubricating viscosity, where the amounts of the additive components are in percent by weight, excluding diluent oil:

Example	1	2	3	4
Succinimide dispersant	2.5	2.5	2.5	2.5
Zinc dialkyldithiophosphate	1.0	1.0	1.0	1.0
Antioxidants	0.6	0.6	0.6	0.6
Glycerol monooleate	0.5	0.5	0.5	0.5
400 TBN calcium sulfonate detergent ^a	0.4	0.8	0.7	0.4
300 TBN calcium sulfonate detergent ^a	0.55			
100-150 TBN calcium sulfonate detergent ^b		0.15		
165 TBN calcium detergent, predominantly alkyl salicylate			0.26	
400 TBN calcium detergent, mixture of fatty carboxylate and alkyl phenate				0.7
Test Results, Sequence VIB, ILSAC GF-3				
Initial Fuel Economy (passing = 1.6)	2.0, 1.8, 2.0	1.4	1.6	1.8
Durability (passing = 1.3)	1.5, 1.1, 1.3	n.d.	1.1	1.1

n.d. = not determined

a. A synthetic sulfonate detergent

b. A natural sulfonate detergent

5 **[0065]** The results show that use of a sulfonate detergent in the substantial absence of other detergents can lead to passing values for the Sequence VIB test as defined by the ILSAC GF-3 specification for fuel economy and durability. It is preferable that the sulfonate detergent component is predominantly (≥ 85 or 90% by weight) based on a synthetic detergent, and likewise that it is predominantly (≥ 85 or 90%) a detergent with a high Total Base Number ($\text{TBN} \geq 150$).

10 **[0066]** As used herein, the term "hydrocarbyl substituent" or "hydrocarbyl group" is used in its ordinary sense, which is well-known to those skilled in the art. Specifically, it refers to a group having a carbon atom directly attached to the remainder of the molecule and having predominantly hydrocarbon character. Examples of hydrocarbyl groups include: (1) hydrocarbon substituents, that is,
15 aliphatic (e.g., alkyl or alkenyl), alicyclic (e.g., cycloalkyl, cycloalkenyl) substituents, and aromatic-, aliphatic-, and alicyclic-substituted aromatic substituents, as well as cyclic substituents wherein the ring is completed through another

portion of the molecule (e.g., two substituents together form a ring); (2) substituted hydrocarbon substituents, that is, substituents containing non-hydrocarbon groups which, in the context of this invention, do not alter the predominantly hydrocarbon substituent (e.g., halo (especially chloro and fluoro), hydroxy, alkoxy, mercapto, alkylmercapto, nitro, nitroso, and sulfoxy); (3) hetero substituents, that is, substituents which, while having a predominantly hydrocarbon character, in the context of this invention, contain other than carbon in a ring or chain otherwise composed of carbon atoms. Heteroatoms include sulfur, oxygen, nitrogen, and encompass substituents as pyridyl, furyl, thienyl and imidazolyl.

10 In general, no more than two, preferably no more than one, non-hydrocarbon substituent will be present for every ten carbon atoms in the hydrocarbonyl group; typically, there will be no non-hydrocarbon substituents in the hydrocarbonyl group.

[0067] It is known that some of the materials described above may interact in the final formulation, so that the components of the final formulation may be different from those that are initially added. For instance, metal ions (of, e.g., a detergent) can migrate to other acidic sites of other molecules. The products formed thereby, including the products formed upon employing the composition of the present invention in its intended use, may not be susceptible of easy description. Nevertheless, all such modifications and reaction products are included within the scope of the present invention; the present invention encompasses the composition prepared by admixing the components described above.

[0068] Each of the documents referred to above is incorporated herein by reference. Except in the Examples, or where otherwise explicitly indicated, all numerical quantities in this description specifying amounts of materials, reaction conditions, molecular weights, number of carbon atoms, and the like, are to be understood as modified by the word "about." Unless otherwise indicated, each chemical or composition referred to herein should be interpreted as being a commercial grade material which may contain the isomers, by-products, derivatives, and other such materials which are normally understood to be present in the commercial grade. However, the amount of each chemical component is presented exclusive of any solvent or diluent oil which may be customarily present in the commercial material, unless otherwise indicated. It is to be understood that the upper and lower amount, range, and ratio limits set forth herein may be independently combined. As used herein, the expression "consisting essentially of" permits the inclusion of substances which do not materially affect the basic and novel characteristics of the composition under consideration.

What is claimed is:

1. A composition suitable for lubricating an internal combustion engine, comprising:
 - 5 (a) an oil of lubricating viscosity;
 - (b) an overbased detergent, wherein the detergent is exclusively or predominantly a linear alkylbenzenesulfonate detergent having a metal ratio of at least about 8, wherein in said composition the amount of phenate detergent is less than about 15% by weight of the total amount of detergents
 - 10 (c) a combination of antioxidants comprising
 - (i) about 0.1 to about 2 weight percent hindered phenolic ester antioxidant and
 - (ii) about 0.2 to about 2 weight percent aromatic amine antioxidant; and
 - 15 (d) at least one further component selected from the group consisting of dispersants, zinc dialkyldithiophosphates, and friction modifiers.
2. The composition of claim 1 wherein the detergent is exclusively or predominantly a calcium overbased synthetic linear alkylbenzenesulfonate detergent, the alkylbenzene group in said detergent having a number average
20 molecular weight of about 320 to about 700.
3. The composition of claim 2 wherein the composition contains less than about 500 parts per million by weight of metals other than calcium or zinc.
4. The composition of claim 1 further comprising at least one salicylate detergent, saligenin detergent, or salixarate detergent.
- 25 5. The composition of claim 1 wherein the amount of any detergent other than the alkylbenzenesulfonate detergent is less than about 15% of the amount of the total amount of detergents.
6. The composition of claim 1 wherein the amount of any phenate detergent is less than about 1% by weight of the total amount of detergents.
- 30 7. The composition of claim 1 wherein the composition comprises a zinc dialkyldithiophosphate wherein said alkyl groups are predominantly secondary,

in an amount to deliver about 0.025 to about 0.1 weight percent phosphorus to the composition.

8. The composition of claim 1 wherein the antioxidant component (c) further comprises about 0.1 to about 1 weight percent of a sulfurized olefin.

5 9. The composition of claim 8 wherein the sulfurized olefin is sulfurized 4-carbobutoxy cyclohexene.

10. A composition prepared by admixing the components of claim 1.

11. A method for lubricating an internal combustion engine, comprising supplying thereto the composition of claim 1.

10 12. A composition suitable for lubricating an internal combustion engine, comprising:

(a) an oil of lubricating viscosity;

(b) an overbased detergent, wherein the detergent is exclusively or predominantly a synthetic linear alkylbenzenesulfonate detergent having a metal
15 ratio of at least about 8 and the alkylbenzene group therein having a number average molecular weight of about 320 to about 700, wherein in said composition the amount of phenate detergent is less than about 1% by weight of the total amount of detergents and the total amount of detergents other than the alkylbenzenesulfonate is less than about 15% by weight of the total amount of detergents;

20 (c) a combination of antioxidants comprising

(i) about 0.1 to about 2 weight percent hindered phenolic ester antioxidant,

(ii) about 0.2 to about 2 weight percent aromatic amine antioxidant, and

25 (iii) about 0.1 to about 1 weight percent of a sulfurized olefin antioxidant; and

(d) a zinc dialkyldithiophosphate wherein said alkyl groups are predominantly secondary, in an amount to deliver about 0.025 to about 0.1 weight percent phosphorus to the composition;

30 wherein the composition contains less than about 300 parts per million by weight of metals other than calcium or zinc.

13. A concentrate comprising

- (a) a concentrate-forming amount of an oil of lubricating viscosity;
- (b) an overbased detergent, wherein the detergent is exclusively or predominantly a linear alkylbenzenesulfonate detergent having a metal ratio of about at least about 8 and the alkylbenzene group therein having a number
5 average molecular weight of about 320 to about 700, wherein in said composition the amount of phenate detergent is less than about 15% by weight of the total amount of detergents;
- (c) a combination of antioxidants comprising
 - (i) hindered phenolic ester antioxidant and
 - 10 (ii) aromatic amine antioxidant; and
- (d) at least one further component selected from the group consisting of dispersants, zinc dialkyldithiophosphates, and friction modifiers.

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 May 2003 (15.05.2003)

PCT

(10) International Publication Number
WO 2003/040273 A3

(51) International Patent Classification⁷: **C10M 163/00** //
(C10M 163/00, 159:24, 159:22, 129:10, 129:76, 133:12,
135:04, 135:06, 137:10), C10N 10/04, 40/25

(74) Agents: **SHOLD, David, M.** et al.; The Lubrizol Corpo-
ration, 29400 Lakeland Boulevard, Wickliffe, OH 44092-
2298 (US).

(21) International Application Number:
PCT/US2002/033117

(22) International Filing Date: 15 October 2002 (15.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/337,720 5 November 2001 (05.11.2001) US

(71) Applicant (for all designated States except US): **THE LU-
BRIZOL CORPORATION** [US/US]; 29400 Lakeland
Boulevard, Wickliffe, OH 44092-2298 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WILK, Melody, A.**
[US/US]; 90 East Shore Boulevard, Timberlake, OH 44095
(US). **DOHNER, Brent, R.** [US/US]; 10320 Springbrook
Court, Concord, OH 44077 (US). **ZALAR, Frank, V.**
[US/US]; 13619 Fox Hills Drive, Novelty, OH 44072
(US). **KELLEY, Jack, C.** [US/US]; 8860 Peppermill Run,
Chagrin Falls, OH 44023 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE, SK, TR).

Published:

— with international search report

(88) Date of publication of the international search report:
11 March 2004

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: LUBRICATING COMPOSITION WITH IMPROVED FUEL ECONOMY

(57) Abstract: A composition for lubricating an internal combustion engine includes an oil of lubricating viscosity; a predominantly linear alkylbenzenesulfonate detergent having a metal ratio of at least 8; and a combination of hindered phenolic ester antioxidant and aromatic amine antioxidant. The amount of any phenate detergent is less than 15% by weight of the total amount of detergents.

WO 2003/040273 A3

INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/US 02/33117

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10M163/00 //(C10M163/00, 159:24, 159:22, 129:10, 129:76, 133:12,
135:04, 135:06, 137:10), C10N10:04, 40:25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 44419 A (LUBRIZOL CORP ;WILK MELODY A (US)) 21 June 2001 (2001-06-21) examples A1,A2,A3 example I page 50, line 8 -page 50, line 12 ---	1-12
X	US 5 422 022 A (CHAMBERLIN III WILLIAM B) 6 June 1995 (1995-06-06) column 2, line 48 -column 3, line 14 examples 1-3 column 60, line 36 -column 60, line 39 --- -/--	1-12



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

3 April 2003

Date of mailing of the international search report

09/04/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Perakis, N

INTERNATIONAL SEARCH REPORT

Internat. Application No

PCT/US 02/33117

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 490 945 A (SMITH THOMAS R ET AL) 13 February 1996 (1996-02-13) column 4, line 9 -column 4, line 16 example C2 column 47, line 53 -column 47, line 65 column 53, line 33 -column 55, line 41 tables I,L column 70, line 47 -column 71, line 8 ---	1-12
X	US 4 952 328 A (SCHROECK CALVIN W ET AL) 28 August 1990 (1990-08-28) cited in the application column 2, line 63 -column 3, line 30 column 28, line 59 -column 29, line 24 examples C1-C13 column 41, line 31 -column 43, line 20 column 66, line 23 -column 66, line 68 tables I,II,III column 75, line 45 -column 75, line 54 ---	1-12
X	US 4 326 972 A (CHAMBERLIN III WILLIAM B) 27 April 1982 (1982-04-27) cited in the application abstract column 1, line 41 -column 2, line 21 column 3, line 62 -column 5, line 20 column 6, line 50 -column 6, line 53 example 2 tables III,IV ---	1-12
A	US 5 562 864 A (SALOMON MARY F ET AL) 8 October 1996 (1996-10-08) examples C-2 column 3, line 53 -column 4, line 17 examples D9-D19 column 46, line 53 -column 46, line 65 column 52, line 36 -column 53, line 60 ---	1-12
A	US 5 614 480 A (SALOMON MARY F ET AL) 25 March 1997 (1997-03-25) column 3, line 53 -column 4, line 19 examples C9-C19 examples E-3 column 46, line 65 -column 49, line 28 column 59, line 8 -column 59, line 51 -----	1-12

INTERNATIONAL SEARCH REPORT

on on patent family members

Internat application No

PCT/US 02/33117

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0144419	A	21-06-2001	AU 2259401 A EP 1240282 A1 WO 0144419 A1	25-06-2001 18-09-2002 21-06-2001
US 5422022	A	06-06-1995	AT 115176 T AU 625351 B2 AU 6702390 A BR 9100628 A CA 2030481 A1 DE 69014866 D1 DE 69014866 T2 EP 0462319 A1 ES 2067640 T3 FI 910751 A JP 4261495 A NO 905227 A	15-12-1994 09-07-1992 02-01-1992 07-04-1992 21-12-1991 19-01-1995 04-05-1995 27-12-1991 01-04-1995 21-12-1991 17-09-1992 23-12-1991
US 5490945	A	13-02-1996	AU 663123 B2 AU 2785192 A BR 9206248 A CA 2102893 A1 EP 0596047 A1 FI 940194 A JP 7500375 T MX 9207084 A1 NO 934453 A WO 9323505 A1 US 5562864 A AT 133702 T AU 657988 B2 AU 2233892 A BR 9205244 A CA 2085614 A1 DE 69208009 D1 EP 0535221 A1 ES 2085628 T3 FI 925777 A JP 5508188 T MX 9201753 A1 NO 924807 A WO 9218589 A2 US 5614480 A US 5486300 A AT 146215 T AU 657333 B2 AU 1918992 A BR 9205241 A CA 2085615 A1 DE 69215819 D1 DE 69215819 T2 EP 0535217 A1 ES 2097912 T3 FI 925775 A JP 5508186 T NO 924902 A WO 9218588 A1	28-09-1995 13-12-1993 25-04-1995 16-11-1993 11-05-1994 14-01-1994 12-01-1995 01-11-1993 07-12-1993 25-11-1993 08-10-1996 15-02-1996 30-03-1995 17-11-1992 27-07-1993 20-10-1992 14-03-1996 07-04-1993 01-06-1996 18-12-1992 18-11-1993 01-10-1992 11-12-1992 29-10-1992 25-03-1997 23-01-1996 15-12-1996 09-03-1995 17-11-1992 27-07-1993 20-10-1992 23-01-1997 10-07-1997 07-04-1993 16-04-1997 18-12-1992 18-11-1993 10-02-1993 29-10-1992
US 4952328	A	28-08-1990	AT 103968 T	15-04-1994

INTERNATIONAL SEARCH REPORT

on on patent family members

Internat application No

PCT/US 02/33117

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4952328	A		AU 613193 B2	25-07-1991
		AU 3518689 A	30-11-1989	
		BE 1001976 A3	02-05-1990	
		BR 8902900 A	18-09-1990	
		CA 1333595 A1	20-12-1994	
		CH 678731 A5	31-10-1991	
		CN 1042176 A ,B	16-05-1990	
		DE 3917394 A1	07-12-1989	
		DE 68914439 D1	11-05-1994	
		DE 68914439 T2	20-10-1994	
		DK 257689 A	28-11-1989	
		EP 0394377 A1	31-10-1990	
		ES 2012722 A6	01-04-1990	
		FI 892553 A	28-11-1989	
		FR 2631969 A1	01-12-1989	
		GB 2219306 A ,B	06-12-1989	
		HK 66891 A	30-08-1991	
		HU 55046 A2	29-04-1991	
		IL 90401 A	18-08-1992	
		IN 175024 A1	22-04-1995	
		IT 1231516 B	07-12-1991	
		JP 2028294 A	30-01-1990	
		JP 2796356 B2	10-09-1998	
		KR 9306822 B1	24-07-1993	
		MX 166364 B	05-01-1993	
		NL 8901328 A	18-12-1989	
		NO 892127 A	28-11-1989	
		RO 109749 B1	30-05-1995	
		SE 8901894 A	28-11-1989	
		SG 62591 G	23-08-1991	
		WO 8911519 A1	30-11-1989	
		RU 2023003 C1	15-11-1994	
		ZA 8904014 A	25-04-1990	
US 4326972	A	27-04-1982	CA 1123820 A1	18-05-1982
			ES 481554 A1	16-06-1980
			FR 2428668 A1	11-01-1980
			GB 2023169 A ,B	28-12-1979
			IN 150959 A1	29-01-1983
			JP 55040764 A	22-03-1980
MX 150323 A				17-04-1984
US 5562864	A	08-10-1996	AU 663123 B2	28-09-1995
			AU 2785192 A	13-12-1993
			BR 9206248 A	25-04-1995
			CA 2102893 A1	16-11-1993
			EP 0596047 A1	11-05-1994
			FI 940194 A	14-01-1994
			JP 7500375 T	12-01-1995
			MX 9207084 A1	01-11-1993
			NO 934453 A	07-12-1993
			WO 9323505 A1	25-11-1993
			US 5490945 A	13-02-1996
			AT 133702 T	15-02-1996
			AU 657988 B2	30-03-1995
			AU 2233892 A	17-11-1992
			BR 9205244 A	27-07-1993
			CA 2085614 A1	20-10-1992

INTERNATIONAL SEARCH REPORT

on on patent family members

Internatly .pplication No

PCT/US 02/33117

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5562864	A	DE 69208009 D1	14-03-1996
		EP 0535221 A1	07-04-1993
		ES 2085628 T3	01-06-1996
		FI 925777 A	18-12-1992
		JP 5508188 T	18-11-1993
		MX 9201753 A1	01-10-1992
		NO 924807 A	11-12-1992
		WO 9218589 A2	29-10-1992
		US 5614480 A	25-03-1997
		US 5486300 A	23-01-1996
		AT 146215 T	15-12-1996
		AU 657333 B2	09-03-1995
		AU 1918992 A	17-11-1992
		BR 9205241 A	27-07-1993
		CA 2085615 A1	20-10-1992
		DE 69215819 D1	23-01-1997
		DE 69215819 T2	10-07-1997
		EP 0535217 A1	07-04-1993
		ES 2097912 T3	16-04-1997
		FI 925775 A	18-12-1992
		JP 5508186 T	18-11-1993
		NO 924902 A	10-02-1993
		WO 9218588 A1	29-10-1992
US 5614480	A	25-03-1997	AU 2891592 A
			BR 9206247 A
			CA 2102892 A1
			EP 0596048 A1
			FI 940193 A
			JP 7500374 T
			MX 9206986 A1
			NO 934454 A
			WO 9323504 A1
			AT 133702 T
			AU 657988 B2
			AU 2233892 A
			BR 9205244 A
			CA 2085614 A1
			DE 69208009 D1
			EP 0535221 A1
			ES 2085628 T3
			FI 925777 A
			JP 5508188 T
			MX 9201753 A1
			NO 924807 A
			WO 9218589 A2
			US 5490945 A
			US 5486300 A
			US 5562864 A
			AT 146215 T
			AU 657333 B2
			AU 1918992 A
			BR 9205241 A
			CA 2085615 A1
			DE 69215819 D1
			DE 69215819 T2
			EP 0535217 A1
			ES 2097912 T3

INTERNATIONAL SEARCH REPORT

on on patent family members

Internat pplication No

PCT/US 02/33117

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5614480	A	FI 925775 A	18-12-1992
		JP 5508186 T	18-11-1993
		NO 924902 A	10-02-1993
		WO 9218588 A1	29-10-1992
<hr/>			

THIS PAGE BLANK (USPTO)